Preliminary Amendment of U.S. National Stage for International Application PCI/EP2005/011071 filed October 14, 2005

Amendments to the Claims

The following Listing of Claims replaces all pending claims in the application.

Listing of Claims:

1-10. (Cancelled).

11. (New) An ethoxylated derivative of an amidoamine according to the general formula (1):

$$R^{1}$$
-CO-NR²-[(CH₂),-NR²],,-CO-R⁴ (1)

in which R¹, R², R³ and R⁴ independently of one another represent a hydrogen atom, a branched or unbranched alkyl or alkenyl group containing 5 to 23 carbon atoms or a CO-CH-CH-COOH group and n is a number of 1 to 6 and m is a number of 1 to 8, as an emulsifier in drilling fluids which contain at least one continuous oil phase, an aqueous phase and additives.

- 12. (New) The derivative according to Claim 11, wherein the derivative contains 1 to 10 parts ethylene oxide per part amidoamine according to formula (1).
- 13. (New) The derivative according to Claim 11, wherein the derivative contains 1 to 7 parts ethylene oxide per part amidoamine according to formula (1).
- 14. (New) The derivative according to Claim 11, wherein the derivative contains 1 to 5 parts ethylene oxide per part amidoamine according to formula (1).

Preliminary Amendment of U.S. National Stage for International Application PCT/EP2005/011071 filed October 14, 2005

- 15. (New) The derivative according to Claim 11, wherein R and R represent an alky) and/or alkenyl group containing 5 to 23 carbon atoms and R is a CO-CH=CH-COOH group and/or hydrogen atom.
- 16. (New) The derivative according to Claim 11, wherein the compound according to formula (1) is produced by reaction of a tall oil fatty acid with an oligo- or polyethylene amine.
- 17. (New) The derivative according to Claim 16, wherein the polyethylene amine is selected from the group consisting of diethylene triamine, triethylene tetramine, tertacthylene pentamine, and mixtures thereof.
- 18. (New) The derivative according to Claim 11, present as an emulsifier in a drilling fluid in an amount of about 0.1 to 25% by weight of the total weight of drilling fluid.
- 19. (New) The derivative according to Claim 11, present as an emulsifier in a drilling fluid in an amount of about 0.1 to 10% by weight of the total weight of drilling fluid.
- 20. (New) The derivative according to Claim 11, present as an emulsifier in a drilling fluid in an amount of about 0.1 to 5% by weight of the total weight of drilling fluid.
- 21. (New) The derivative according to Claim 11, wherein the drilling fluid is a water-in-oil fluid.
- (New) The derivative according to Claim 11, wherein the drilling fluid further comprises a component selected from the group consisting of: a weighting agent, a fluid loss additive, a wetting agent, an alkali reserve, a thickener, a biocide and mixtures thereof.

Preliminary Amendment of U.S. National Stage for International Application PCT/EP2005/011071 filed October 14, 2005

- 23. (New) The derivative according to Claim 11, wherein the derivative is produced by reaction of amidoamines according to formula (1) with ethylene oxide at temperatures of 100 to 150°C in the presence of a catalyst selected from the group consisting of potassium hydroxide or sodium methylate.
- (New) The derivative according to Claim 11, wherein the derivative is produced by reaction of amidoamines according to formula (1) with ethylene oxide at temperatures of 110 to 140°C in the presence of a catalyst selected from the group consisting of potassium hydroxide or sodium methylate.
- 25. (New) A composition, comprising;
 an ethoxylated derivative of an amidoamine according to the general formula (1);

$$R^3$$
-CO-NR 3 -[(CH₂),-NR 3],,-CO-R 4 (1)

in which R¹, R², R³ and R³ independently of one another represent a hydrogen atom, a branched or unbranched alkyl or alkeryl group containing 5 to 23 carbon atoms or a CO-CH-CH-COOH group and n is a number of 1 to 6 and m is a number of 1 to 8; and

a confinuous oil phase in admixture with a limited quantity of a disperse aqueous phase (w/o invert type).

- 26. (New) The composition according to Claim 25, further comprising a component selected from the group consisting of a weighting agent, a fluid loss additive, a wetting agent, an alkali reserve, a thickener, a biocide and mixtures thereof.
- 27. (New) The composition according to Claim 25, wherein the continuous oil phase is selected from a group consisting of.

Preliminary Amendment of U.S. National Stage for International Application PCT/EP2005/011071 filed October 14, 2005

- (a) carboxylic acid esters corresponding to formula (II): R'-COO-R" (II)
 where R' is saturated or unsaturated, linear or branched C_{5.25} alkyl group and R" is
 a C_{1.22} alkyl group which may be saturated or unsaturated, linear or branched;
 - (b) linear or branched Cs.30 olefins;
- (c) water-insoluble, symmetrical or nonsymmetrical ethers of monohydric alcohols of natural or synthetic origin which may contain 1 to 24 carbon atoms;
- (d) water-insoluble alcohols corresponding to formula (III): R^{***} -OH where R^{***} is a saturated, unsaturated, linear or branched $C_{8,24}$ alkyl group;
 - (c) carbonic acid esters,
 - (f) paraffins, and
 - (g) acetals.